

INDEPENDENCE 323

MAST

- Hydraulically Raised NOV® Ideal
- 142' Height
- 750,000 lbs. Static Hook

SUBSTRUCTURE

- Hydraulically Raised NOV® Ideal
- 25' Floor Height (RKB)
- 22'-6" Clear Height (RBC)
- 37'-1/2" Rotary Table
- Setback Capacity: 750,000 lbs.
- Racking Capacity: 28,700' (5.5" DP)

WALKING SYSTEM

- Hydraulic, Remote Controlled Stompers
- 200' Max (X)*
- 35' Max (Y)
- Integrated Cable Management System
- Custom Engineered Flowline

DRAWWORKS

- 2,000 HP Dual Speed -NOV®
- (1) 2,000 HP AC Motor

TRAVELING BLOCK ASSEMBLY

- 500 Ton NOV® TDS-11SH AC Top Drive
- 51,000 ft.-lbs. Torque @ 110 RPM
- 500 Ton Traveling Block

PIPE HANDLING EQUIPMENT

- Forum® FR120 Iron Roughneck
- Canrig® Hydraulic Catwalk

ENGINE PACKAGE

- (4) CAT® 3512C Diesel Engines
- (4) 1750 kVa Generator Sets
- Bi-Fuel Equipped

CONTROL SYSTEM

- NOV® Amphion Drive House
- Drillers Cabin w/NOV® Amphion Chair

MUD PUMPS

- (3) 1,600 HP Triplex - 7,500 PSI
- DC Pumps w/ NOV® SCR Controls

MUD SYSTEM

- 1000 BBL. Pit Capacity - 7,500 PSI
- (3) Derrick® Hyperpool Shakers
- Vacuum Degasser
- Desander
- Desilter
- MGS 600 GPM 48" D / 14'-10" L

MUD MIXING EQUIPMENT

- (1) Chemical Mixing Hoppers
- Caustic Barrel

LIQUID STORAGE

- 500 BBL. Water Storage Tank
- 500 BBL. Diesel Storage Tank

BOP EQUIPMENT

- Trolley Beam Handling System
- (2) Hydraulic Winches
- 13-5/8" x 5,000 PSI, Annular
- 13-5/8" x 10,000 PSI, Single Ram
- 13-5/8" x 10,000 PSI, Double Ram
- 2-1/16" x 4-1/16" 10,000 PSI Choke Manifold
- (1) 7 Station Accumulator Skid

NDS® OFFERINGS

- ROCKit (Oscillator)
- REVit Z Torque (Stickslip Mitigation)

NOV® OFFERINGS

- NOVOS Capable

TUBULARS

- Available at Operator's Request



INDEPENDENCE
CONTRACT DRILLING